## **COLLY** [S3L FO SR]

**UNISEX: 75659 BLACK/WHITE** 

## 



|  | DATA GUIDE                           |  |
|--|--------------------------------------|--|
| Certification:                         | EN ISO 20345:2022 [S3L FO            | SR]  |
| Upper Material:                        | Recycled Microfibre                  |  |
| Lining Material:                       | Recycled Polyester                   |  |
| Midsole Material:                      | Recycled EVA                         |  |
| Outsole Material:                      | Rubber                               |  |
| Safety Toe Cap:                        | Composite                            | 763143                                       |
|  |                                      |  |
|  |                                      | Click or scan QR code<br>to view certificate |
| ESTING THE SLIP RES<br>FOUR SFC OUTSOL |                                      |  |
| TANDARD REQUIREMEN                     | T SR REQUIREMENT                     |  |
| x222% x1<br>0.69 0.4                   | 89%<br><sup>58</sup><br>0.42<br>0.44 | 0%   |

0.19

Ceramic +

Glycerine

Forward

heel slip

Ceramic +

Sodium Laurvl

Sulphate

Backward forepart slip

Shoes For Crews outsole Industry standard

Slip resistance test according to EN ISO 20344:2021, conducted by Intertek Testing Services Shenzhen Ltd., in August 2022; on a scale of 0.0 (without slip resistance) to 1.0 (very high level of slip resistance, e. g. on dry carpeted floors). All SFC shoes are fitted with the patented, slip-resistant Shoes For Crews outsole Tested product: Carrig Low 62201.



0.22

Ceramic +

Glycerine

Backward

forepart slip