GUARDIAN [S4 SRC]

S4 (또 胀 EN ISO 20345:2011 [S4 SRC] **UNISEX: 2018 GREEN SIZE:** EU 37-48 UK 37-48 DATA GUIDE WATERPROOF upper to permanently repel ٥ water and keep your feet dry EN ISO 20345:2011 [S4 SRC] Certification: 2 **STEEL SAFETY TOE - 200 joules PVC upper** Lining Material: Polyester Midsole Material: PVC Regular fit Outsole Material: Rubber **Polyester lining** Click or scan QR code TESTING THE SLIP RESISTANCE to view certificate OF OUR SFC OUTSOLE [EN ISO 20344:2021] × **EXTREMELY SLIP-RESISTANT OUTSOLE** Exceeds the industry norm SR STANDARD REQUIREMENT SR REQUIREMENT according to EN ISO 20344:2021 **x189%** slip resistance test - Larger surface covered by the outsole Antistatic property provides better slip-resistance **x200%** x221% 0.36 **CLOG-RESISTANT OUTSOLE** 0.31 Shoes For Crews outsole Traction lugs have wide spacing which Industry standard 0.22 0.19 won't let dirt and debris get stuck in the outsole Slip resistance test according to EN ISO 20344:2021, conducted by Intertek Testing Services Shenzhen Ltd., in August 2022; on a scale of 0.0 (without slip Ceramic + Ceramic + Ceramic + Ceramic + resistance) to 1.0 (very high level of slip resistance, e. Sodium Laurvl Sodium Laurvl Glycerine Glycerine g. on dry carpeted floors). All SFC shoes are fitted with Sulphate Sulphate Forward Backward the patented, slip-resistant Shoes For Crews outsole Forward heel slip Backward forepart slip heel slin forepart slip Tested product: Carrig Low 62201. Energy absorbing Fuel resistant heel construction Removable cushioned insole - recycled EVA SHOES Weight (per shoe): 840 grams Also available: (based on size 38) SHUES 40 cm shaft height FOR CREWS Guardian White/Blue: 2017B